

IXOLIFT X500E-SP

Self-Propelled & Push Around Combo

- Low maintenance
- Simple and safe to use
- Automatic parking brakes
- Safe alternative to ladders
- Working height up to 5 meters
- Fits through doorways and in elevators
- Low entry, Low Weight, Small turning radius
- Compact sized, easy to drive or move around alone
- Engine decoupling changes from Self-propelled to Push-around



TECHNICAL SPECIFICATIONS	IXOLIFT X500E-SP	
Working height	4950 mm	
Max working load	180 kg	
Max platform height	2950 mm	
Platform size	530 x 760 mm	
Guardrail height	1100 mm	
Stowed height	1640 mm	
Stowed length	1200 mm	
Stowed width	760 mm	
Total weight	320 kg	
Driving speed	Raised, 2 km/h	Lowered, 4 km/h
Lifting speed	16 s	
Power source	2pc, 75 Ah, 12V batteries, maintenance free	
Wheels	Polyurethane coating, leaves no marks	
CE Marking	Machinery Directive 2006/42/EC EN 280:2013 + A1:2015	



Decoupling



USB Socket



Self-Propelled



Push Around

2019 / v1.00



IXOLIFT Ltd | Kalkkimäentie 2 | FI-03100 Nummela, FINLAND
+358 20 741 5010 | sales@ixolift.com | www.ixolift.com