

IXOLIFT®
LIFTING LIVES

IXOLIFT X400 INOX

**STAINLESS ACCESS FOR THE
HARSHEST ENVIRONMENT**



ADJUSTABLE WORK PLATFORM

SAFER ACCESS, OFFSHORE AND ONSHORE

Up to four metres of working height with both hands free – in acid-proof AISI 316 stainless steel for offshore, energy and other harsh environments.





IXOLIFT X400 INOX

ADJUSTABLE WORK PLATFORM

Familiarity should not be mistaken for safety. The **IXOLIFT X400 INOX** gives up to four metres of working height with both hands free – in acid-proof AISI 316 stainless steel that stands up to salty air, wind and the demands of offshore and onshore energy sites.

01

ADJUSTABLE HEIGHT

Stop exactly where the job is.

The raising handle locks the platform at the height you need. Patented gas spring powered height adjustment – maintenance free.

03

LOWER RUNNING COSTS

Quick set up, less to maintain.

Roll in, adjust height, get to work. No charging, no hydraulic oil – maintenance free. Just 728 mm wide, it goes where a scaffold won't.

05

ATEX CERTIFIED

Built for hazardous zones.

Every X400 INOX is ATEX-marked for Zones 1 and 21, where explosive gas or dust can occur.

CHOOSE LADDERS LAST.
WHY BUILD A SCAFFOLD
FOR A ONE-MAN JOB?

02

ALL-ROUND SAFETY

Guarded on every side, hands free.

Guardrails all round, so both hands stay on the job. Automatic anti-surfing brakes engage once the platform rises.

04

ACID-PROOF STAINLESS

AISI 316 stainless steel.

Corrosion resistant in salty, offshore air – a long-life, low-maintenance frame for offshore and onshore energy sites.

06

MADE IN FINLAND

To ISO standards.

Every X400 INOX is designed and manufactured to international quality and environmental management standards (ISO 9001 and ISO 14001).



COMPACT SIZE



AUTOMATIC BRAKES



GAS SPRING POWERED



TOOL TRAY

TECHNICAL SPECIFICATIONS

IXOLIFT X400WS INOX

SPECIFICATION	X400WS INOX
Working height	3974 mm
Max working load	150 kg
Max platform height	1974 mm
Min platform height	974 mm
Platform size	526 x 556 mm
Stowed height	1970 mm
Stowed length	1198 mm
Stowed width	728 mm
Total weight	240 kg
Max length with stabilisers out	1500 mm
Max width with stabilisers out	1668 mm
Wind rating	12,5 m/s
Height adjustment	Patented gas spring
CE marking	
Machinery Directive 2006/42/EC EN 280:2013 + A1:2015 except §5.6.2 Guardrails based on EN 131-7 §5.6	
ATEX marking	
ATEX Directive 2014/34/EU Ex h IIC T6 Gb & Ex h IIIC T60°C Db	



PATENTED



BUILT FOR ENERGY SITES

12,5 m/s

WIND RATING

X400WS INOX with stabilisers out, for outdoor decks.

AISI 316

ACID-PROOF STAINLESS STEEL

Rust-resistant in salty, offshore air.

Zones 1 & 21

ATEX AS STANDARD

For areas where explosive gas or dust can occur.

X400WS INOX: max load 150 kg, working height up to 4 m | CE, ISO 9001, ISO 14001, made in Finland

WE ARE **IXOLIFT**®

OUR MISSION IS TO PROVIDE THE WORLD WITH A SAFE AND SMART ALTERNATIVE TO LADDERS AND SCAFFOLDS.

IXOLIFT products are designed to meet a variety of safety regulations, which allows them to be used just about anywhere. They are easy to use, maintain and manoeuvre.

Safety doesn't just come first.
Safety is IXOLIFT's mission.

IXOLIFT Ltd

Kalkkimäentie 2, FI-03100 Nummela, Finland

+358 20 741 5010 | sales@ixolift.com

www.ixolift.com

Subject to change without notice. V101.2026